



Products & Services

Pipe, Tube, Fabrication

Our Products

BBL Co. is a leading distributor of steel, pipe, tubing, and fabrication for commercial, industrial and military installations. We ship across the U.S. and globally, and can deliver to the Northeast and Mid-Atlantic regions within 24 hours. We store inventory indoors to maintain mill condition.

| Carbon Steel Pipe | Carbon & Carbon Alloy Steel Tubing | Stainless Steel, Nickel, and Nickel Alloy Pipe & Tubing | Aluminum Pipe & Tubing |
|--|---|--|--|
| <ul style="list-style-type: none">• Seamless Grade B/C<ul style="list-style-type: none">• A-106• A-53• API-5L• ERW (Electric Resistance Weld)<ul style="list-style-type: none">• A-53, Grade B• API-5L• Continuous Weld<ul style="list-style-type: none">• A-53, Type F | <ul style="list-style-type: none">• HREW (Hot Rolled Electric Welded)• DOM (Drawn Over Mandrel)• SMLS (Seamless)• Specifications:<ul style="list-style-type: none">• 1010 - 1018• 1020 - 1026• 4130 - 4140 | <ul style="list-style-type: none">• Specifications:<ul style="list-style-type: none">• 304 - 304L• 316 - 316L• 446• 400, 600, 800• Alloy 20, 625, C276 | <ul style="list-style-type: none">• Specifications:<ul style="list-style-type: none">• 6061• 6063• 2024• 7075 |

**Call us for pipe and tubing;
count on us for quality, service & integrity.**

1.800.523.2284

Our Services

| | |
|---|--|
| <ul style="list-style-type: none">• Saw cutting up to 24" OD• Torch cutting up to 26" OD• Packaging to customer requirements• Beveling up to 26"• Grooving up to 24"• Threading 1/8" to 4" | <ul style="list-style-type: none">• Welding, Fabrication, non-code and ASME code specifications• Custom painting, markings, stenciling, and vibro-etch• Military MIL-P-24691• DCAS approved MIL-I-45208A• ASME QC procedures for quality assurance• EDI systems capabilities; EFT available |
|---|--|



Visit : www.bblco.com
Mail : BBL, Co. 2194 Detwiler Road • PO Box 310 • Kulpville, PA 19443
Call : 215-362-1000 or 800-523-2284 • Fax : 215-256-0524



We accept Visa and Mastercard.

Dimension & Weight Chart

Common Specifications



| Pipe Size | O.D. in Inches | 10 | 0.188 | 20 | 30 | STD | 40 | 60 | XS | 80 | 100 | 120 | 140 | 160 | XXS |
|-----------|----------------|-----------------------|-----------------------|-----------------------|-----------------------|-----------------------|-----------------------|-----------------------|-----------------------|-----------------------|-----------------------|-----------------------|-----------------------|-----------------------|-----------------------|
| | | Wall / In. Wt./Ft. | Wall / In. Wt./Ft. | Wall / In. Wt./Ft. | Wall / In. Wt./Ft. | Wall / In. Wt./Ft. | Wall / In. Wt./Ft. | Wall / In. Wt./Ft. | Wall / In. Wt./Ft. | Wall / In. Wt./Ft. | Wall / In. Wt./Ft. | Wall / In. Wt./Ft. | Wall / In. Wt./Ft. | Wall / In. Wt./Ft. | Wall / In. Wt./Ft. |
| 1/8 | 0.405 | | | | | .068 .24 | .068 .24 | | .095 .31 | .095 .31 | | | | | |
| 1/4 | 0.540 | | | | | .088 .43 | .088 .43 | | .119 .54 | .119 .54 | | | | | |
| 3/8 | 0.675 | | | | | .091 .57 | .091 .57 | | .126 .74 | .126 .74 | | | | | |
| 1/2 | 0.840 | | | | | .109 .85 | .109 .85 | | .147 1.09 | .147 1.09 | | | | .188 1.31 | .294 1.72 |
| 3/4 | 1.050 | | | | | .113 1.13 | .113 1.13 | | .154 1.48 | .154 1.48 | | | | .219 1.95 | .308 2.44 |
| 1 | 1.315 | | | | | .133 1.68 | .113 1.68 | | .179 2.17 | .179 2.17 | | | | .250 2.85 | .358 3.66 |
| 1 1/4 | 1.660 | .109 1.81 | | | | .140 2.27 | .140 2.27 | | .191 3.00 | .191 3.00 | | | | .250 3.77 | .382 5.22 |
| 1 1/2 | 1.900 | .109 2.09 | | | | .145 2.72 | .145 2.72 | | .200 3.63 | .200 3.63 | | | | .281 4.86 | .400 6.41 |
| 2 | 2.375 | .109 2.64 | | | | .154 3.66 | .154 3.66 | | .218 5.03 | .218 5.03 | | | | .344 7.47 | .436 9.04 |
| 2 1/2 | 2.875 | .120 3.53 | .188 5.40 | | | .203 5.80 | .203 5.80 | | .276 7.67 | .276 7.67 | | | | .375 10.02 | .552 13.71 |
| 3 | 3.500 | .120 4.34 | .188 6.66 | | | .216 7.58 | .216 7.58 | | .300 10.26 | .300 10.26 | | | | .438 14.34 | .600 18.60 |
| 3 1/2 | 4.000 | .120 4.98 | .188 7.66 | | | .226 9.12 | .226 9.12 | | .318 12.52 | .318 12.52 | | | | | .636 22.87 |
| 4 | 4.500 | .120 5.62 | .188 8.67 | | | .237 10.80 | .237 10.80 | | .337 15.00 | .337 15.00 | | .438 19.02 | | .531 22.53 | .674 27.57 |
| 5 | 5.563 | .134 7.78 | | | | .258 14.63 | .258 14.63 | | .375 20.80 | .375 20.80 | | .500 27.06 | | .625 32.99 | .750 38.59 |
| 6 | 6.625 | .134 9.30 | .188 12.94 | | | .280 18.99 | .280 18.99 | | .432 28.60 | .432 28.60 | | .562 36.43 | | .719 45.39 | .864 53.21 |
| 8 | 8.625 | .148 13.41 | .188 16.96 | .250 22.38 | .277 24.72 | .322 28.58 | .322 28.58 | .406 25.67 | .500 43.43 | .500 43.43 | .594 51.00 | .719 60.77 | .812 67.82 | .906 74.76 | .875 72.49 |
| 10 | 10.750 | .165 18.67 | .188 21.23 | .250 28.06 | .307 34.27 | .365 40.52 | .365 40.52 | .500 54.79 | .500 54.79 | .594 64.49 | .719 77.10 | .844 89.38 | 1.000 104.23 | 1.125 115.75 | 1.000 104.23 |
| 12 | 12.750 | .180 24.19 | .188 25.25 | .250 33.41 | .330 43.81 | .375 49.61 | .406 53.57 | .562 73.22 | .500 65.48 | .688 88.71 | .844 107.42 | 1.000 125.61 | 1.125 139.81 | 1.312 160.42 | 1.000 125.61 |
| 14 | 14.000 | .250 36.75 | | .312 45.65 | .375 54.62 | .375 54.62 | .438 63.50 | .594 85.13 | .500 72.16 | .750 106.23 | .938 130.98 | 1.094 150.93 | 1.250 170.37 | 1.406 189.29 | |
| 16 | 16.000 | .250 42.09 | | .312 52.32 | .375 62.64 | .375 62.64 | .500 82.85 | .656 107.60 | .500 82.85 | .844 136.74 | 1.031 164.98 | 1.219 192.61 | 1.438 223.85 | 1.594 245.48 | |
| 18 | 18.000 | .250 47.44 | | .312 58.99 | .438 82.23 | .375 70.65 | .562 104.76 | .750 138.30 | .500 93.54 | .938 171.08 | 1.156 208.15 | 1.375 244.37 | 1.562 274.48 | 1.781 308.79 | |
| 20 | 20.000 | .250 52.78 | | .375 78.67 | .500 104.23 | .375 78.67 | .594 123.23 | .812 166.56 | .500 104.23 | 1.031 209.06 | 1.281 256.34 | 1.500 296.65 | 1.750 341.41 | 1.969 379.53 | |
| 22 | 22.000 | .250 58.13 | | .375 86.69 | .500 114.92 | .375 86.69 | .875 197.60 | .500 114.92 | 1.125 251.05 | 1.375 303.16 | 1.625 353.94 | 1.875 403.38 | 2.125 451.49 | | |
| 24 | 24.000 | .250 63.47 | | .375 94.71 | .562 140.81 | .375 94.71 | .688 171.45 | .969 238.57 | .500 125.61 | 1.219 296.86 | 1.531 367.74 | 1.812 429.79 | 2.062 483.57 | 2.344 542.64 | |



Visit : www.bblco.com

Mail : BBL, Co. 2194 Detwiler Road • PO Box 310 • Kulpville, PA 19443

Call : 215-362-1000 or 800-523-2284 • Fax : 215-256-0524

1.800.523.2284